



MACHINE DESCRIPTION

The BUFFERPOS with push over batches pots, barquette or trays on the exit belt so to be removed with the fork.

TECHNICAL DATA	M.U.	BUFFERPOS
HOURLY PRODUCTION	pots/hour	up to 4500
POTS DIAMETER (max)	mm	400
BUFFERPOS WIDTH (standard)	mm	1920
BUFFERPOS LENGHT (standard)	mm	6000
INSTALLED POWER	kW	8
AIR CONSUMPTION (max)	l/min	20
WEIGHT (standard)	kg	1700

TECHNICAL SPECIFICATIONS

- 1 Fix pusher fork.
- 2 Machine controlled by PLC and data display with touch-screen monitor.
- **3** Fencing safety guards with access doors.
- Belts speed adjustable by frequency drive.
- Pneumatic off set control adjustable up to 250 mm.
- Belts and push over motion has electric speed control and encoder for position.
- Radio remote control with start/stop on pots loading phase.
- Available in left and right version.



Pots pusher with 500 mm stroke with electric control and pneumatic stagger (up to 250 mm).



DETAILS



The **positioning** of the pots on the belt can have **a staggered or squared pattern**.

- Buffer belt lenght up to 12 m.
- Buffer belt width up to 3 m.
- Pot collector for an hourly production up to 6000 pots/hour.
- Fix fork.

- **Adjustable** pusher fork.
- Nozzles watering system.
- Positioning wheels.

