



Video



| TECHNICAL DATA | M.U. | LAV10 | LAV10 E |
|---|------------|-----------|-----------|
| HOURLY PRODUCTION (max) | trays/hour | 50 - 600 | 40 - 500 |
| TRAYS DIMENSIONS (max) | mm | 600x400 | 750x500 |
| TRAYS HEIGHT (max) | mm | 150 | 150 |
| WEIGHT | kg | 450 | 450 |
| WATER PUMP (up to 9 bar) | kW | 3,7 | 3,7 |
| WATER COMSUPTION (from 3 bar to 10 bar) | l/min | 157 - 278 | 172 - 305 |
| INSTALLED POWER | kW | 5 | 5 |
| WATER TANK CAPACITY | I | 150 | 150 |
| WASHING NOZZLES | n° | 30 | 34 |
| RINSING NOZZLES | n° | 10 | 12 |
| CONVEYOR BELT LENGTH | mm | 3000 | 3000 |

MACHINE DESCRIPTION

The LAV10 traywasher is suitable for the washing and rinsing of all kinds of trays. The machine is equipped with high pressure water jets, easy to remove for the replacing or cleaning.

The traywasher can be connected to a tunnel for the trays disinfecting or for the UV lamp system both for the thermoformed or injection trays.

TECHNICAL SPECIFICATIONS




Traywasher equipped with disinfecting unit tunnel, wheels, exit table for water draining and second fan for trays drainage.



Thanks to the filter with **extractable drawer**, the machine can be cleaned also **during the working cycle**, without interruptions.

- **1** Pressure wash.
- 2 Flushing.
- 3 Disinfecting unit tunnel for all kinds of trays.
- 4 Hot-galvanised steel base plate.
- **5** Water filter with extractable drawer.
- **6** Fun for trays drainage 2,2 kW.
- **7** Stainless steel vertical multi-stage pump 3,7 kW.
- 8 Discharge for overflowing.
- Top plexiglass door for nozzles inspection.
- Tray washing system with removable nozzles for an easier replacement.
- Water level control with float.
- Frame in AISI 304 stainless steel .



TUNNEL FOR DISINFECTION (accessory)






DETAILS TRAYWASHER





Top plexiglass door for nozzles **inspection**.



The type and placing of the nozzles can be decided by the customer.



Easily **removable** nozzles.



ACCESSORIESTRAYWASHER



- Exit table for water draining.
- **Kit nr. 4 turning stainless steel wheels** diam. 200 mm for traywasher.
- Water heating with electric resistance 8 kW.
- **Tunnel for disinfection** of trays 0,75 kW with filter, tank capacity 48 l, length 1500 mm.
- **Kit nr. 3 stainless steel wheels** (nr. 2 fixed and nr. 1 turning) diam. 200 mm for disinfecting unit tunnel.
- **Second fan** for additional tunnel, for trays draining.
- Tunnel for treatment with nr. 2 UV lamps (6x40 W each).
- Infeed belt.
- Outfeed belt.
- Final balance stacker.



Trays treatment tunnel with **UV lamp system**.





Exit table for water draining.

